


STEEL DOOR & FRAME SYSTEMS, INC.

Standard Features


- 18 and 20 Gauge Cold Rolled or Galvanized Steel
- ◆ Seamless Filled Edges
 (Edge/Corner Seam Construction)
- ◆ Full Body Polystyrene Core
- ♦ Non-Handed Design
- ◆ 12-Gauge Closer Reinforcement
- ◆ 7-Gauge Hinge Reinforcement-Standard / Heavy Duty
- ♦ 16-Gauge Flush Top Cap Galvanized
- ◆ 16-Gauge Inverted Bottom Cap -Galvanized
- ◆ ADA 10 inch Minimum Bottom Rail

- Prime Painted Grey Two Part
 Epoxy Factory Applied, Baked On
- Standard Lock Preparations
 Include 161, Fed 86 Edge,
 Panic Bar Reinforced
- WHI / ITS up to 3 hour,
 Positive Pressure and
 "S" Smoke included
- ◆ STC Rated 28, Model 32-1700 STC Rated 32
- Meets or Exceeds Standards for ANSI 250.4 and ANSI 250.8


Typical Hardware Preparations




ANSI / SDI A115.1 "MB" (MORTISE)



ANSI / SDI A115.2 "C" (BORED)



NON-HANDED HINGE



UNIVERSAL STRIKE A115.1 "U"

