

STEEL DOOR & FRAME SYSTEMS, INC.

Standard Features **Typical** Sections Hardware CLOSED TOP LOCK EDGE ♦ 18-Gauge **Preparations** Galvanized Steel ♦ Seamless Filled Edges ANSI / SDI A115.1 (Edge/Corner Seam Construction) "MB" (MORTISE) ◆ Full Body Polystyrene Core ♦ Non- Handed Design ♦ 12-Gauge Closer Reinforcement ♦ 7-Gauge Hinge Reinforcement-Reversible NON-HANDED HINGE ♦ 16-Gauge Flush Top Cap - Galvanized MINIMUM CORE CLEARANCE 1" Standard / Heavy Duty FROM TOP, ♦ 16-Gauge Inverted Bottom Cap -1/2" AROUND ALL HARDWARE Galvanized ♦ Prime Painted Grey Two Part ANSI / SDI A115.2 "C" (BORED) Epoxy Factory Applied, Baked On ♦ Standard Lock Preparations Include 161, Fed 86 Edge, Panic Bar Reinforced ♦ WHI / ITS up to 3 hour, UNIVERSAL STRIKE A115.1 "U" Positive Pressure and "S" Smoke included HINGE EDGE ♦ Meets or Exceeds Standards for **TOP VIEW** TYPICAL SECTION ANSI 250.4 and ANSI 250.8 N 5 x 20 N 4 x 25 N 3 x 33





